

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	

Commons LED Sconce CMNS Series

Features

Faceted metal housing with dynamic metal faceplate. Vertical or horizontal mounting. For use in hallways, corridors or anywhere general lighting is needed. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

White powder coat.

Diffuser

Faceted metal faceplate.

Electrical

Input 120-277 VAC, 60 Hz LED. LED driver is 0-10V DC dimmable.

LED

Integrated LED modules capable of producing: 13W = 800 lumens 24W = 1600 lumens 3000K (CCT) rated for 50,000 hrs., 90 CRI

Certification

All fixtures are cETLus listed for damp locations. ADA


Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.







Ordering Information:

Source							
White	LED	Lumens	ССТ	н	W	D	
CMNS070708L30D2WH	13W	800	3000K	7"	7"	2"	
CMNS072716L30D2WH	24W	1600	3000K	27"	7"	2"	