

Duncan LED Ceiling DUNF Series

Features

Decorative ceiling fixture features a two-tone metal finish with a gold or white interior effect. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Die-formed steel construction. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Two-tone metal finish in black and gold or black and white.

Diffuser

White acrylic diffuser.

Electrical

Input 120 VAC / 60HZ.

Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120 VAC.

Lamping

Integrated LED modules capable of producing: 26W = 2500 source lumens, 1400 delivered lumens 40W = 4000 source lumens, 2200 delivered lumens Selectable 2700K, 3000K, 3500K, 4000K, 5000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ENERGY STAR® Qualified Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

			Source	Delivered			
Black/Gold	Black/White	LED	Lumens	Lumens	Adjustable CCT	DIA.	D
DUNF15LAJUDBKGD	DUNF15LAJUDBKWH	26W	2500	1400	2700K/3000K/3500K/4000K/5000K	15-1/2"	4"
DUNF20LAJUDBKGD	DUNF20LAJUDBKWH	40W	4000	2200	2700K/3000K/3500K/4000K/5000K	19-1/2"	5"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	













