



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

Armitage LED Pendant AGP Series

Features

Clear or tinted outer glass pendant is suspended with a 9 foot adjustable cord and monopoint canopy. Canopy mounts to a standard junction box (not included).

Construction

The glass cylinder is 8" tall and 10" in diameter and held together into place by stem and top cap. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

The canopy is plated in Satin Nickel.

Diffuser

Glass cylinder pendant is .40" thick. Glass colors include aqua (AQ), clear (CL), clear swirl (CS), and brown (BR).

Electrical

D1 Driver

Direct wired with a constant current low voltage electronic LED driver rated at 120 VAC. The driver is dimmable with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

D2 Driver

Direct wired with a constant current low voltage electronic LED driver rated for 120-277 VAC. LED driver is dimmable 0-10V DC.


Lamping

All pendants include a 6W LED module. Light engine produces 500 source lumens. 3000K and 4000K (CCT). 50,000 hr. LED life, 90 CRI.

Certification

All fixtures are ETL listed for damp locations.

**Specifications and dimensions
subject to change without notice.**



Ordering Information:

10" DIA. x 8" H

Series AGP	Source Lumens 500	LED L	CCT 30 3000K 40 4000K	Driver D1 Voltage (120V TRIAC Dimming) D2 Voltage (120-277V 0-10V Dimming)	Finish SN Satin Nickel	Glass AQ Aqua CC Clear Crackle CL Clear BR Brown
----------------------	-----------------------------	-----------------	------------------------------------	---	----------------------------------	---

Example: AGP500L30D1SNCL