

Ella LED Sconce ELAS Series

FeaturesSimple style elegant geometry. Horizontal or vertical mounting. Provides lighting in residential, commercial and hospitality applications.

Fixture mounts to standard junction box (not included).

Construction Peak plate is die formed of 22 gauge steel. Stand

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black, Satin Brass or Satin Nickel finish.

Diffuser

White acrylic diffusers.

Electrical

Input 120 VAC / 60 Hz. Compatible with residential TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing: 15W = 1100 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.


Certification

All fixtures are cETLus listed for damp locations. ADA Compliant Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.














Ordering Information:

 Black
 Satin Brass
 Satin Nickel
 LED
 LED
 CCT
 H
 W
 D

 ELASO417L30D1BK
 ELASO417L30D1SB
 ELASO417L30D1SN
 15W
 1100
 3000K
 17"
 4-5/8"
 2-3/8"