



Reeves LED Flush Mount RVEF Series

Features

This modern design provides a dramatic look and features ornamental metal accents with a white linen fabric side diffuser. White bottom acrylic diffuser disperses the light. Fixture mounts to standard junction box (not included).

Construction

The canopy is made of 22-gauge cold rolled steel. The LED pan is white painted. The acrylic diffuser is supported by the inner shade. Power supply connections must be made inside a junction box (not included).

Finish

Satin nickel.

Diffuser

White linen fabric side diffuser.
White acrylic bottom diffuser.

Electrical

Input 120-277 VAC 60 HZ.
Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers.
TRIAC and ELV dimming only at 120VAC.

LED

Integrated LED modules capable of producing:
16" - 30W = 2400 lumens
20" - 42W = 3200 lumens
Adjustable Choice 3000K, 3500K, 4000K (CCT).
Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions
subject to change without notice.

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



3in1 color temperature
3000K/3500K/4000K



Ordering Information:

Satin Nickel/Linen White	Source			DIA.	D
	LED	Lumens	Adjustable CCT		
RVEF1624LAJUDSNLW	30W	2400	3000K/3500K/4000K	16"	4"
RVEF2032LAJUDSNLW	42W	3200	3000K/3500K/4000K	20"	4"