

Rosemont LED Pendant RMTP Series

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	

Features

Multi-sided illumination. Includes 9 ft. adjustable cords. For use in kitchen, dining, foyers or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. This fixture mounts to a standard junction box (not included).

Construction

Extruded aluminum housing. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included). Canopy - 1-1/2" H x 8-1/4" DIA.

Finish

Black, Satin Brass or Satin Nickel finish.

Diffuser

White acrylic diffuser.

Electrical

Input 120 VAC 60 HZ. Compatible with TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing: 25W = 1700 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5-year from date-of-purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

				Delivered			
Black	Satin Brass	Satin Nickel	LED	Lumens	CCT	н	DIA.
RMTP08L30D1BK	RMTP08L30D1SB	RMTP08L30D1SN	25W	1700	3000K	24-1/4″	8-1/4″



